



Alternate Daily Cover Specifications

Product Name and Description	Coverone Reinforced PVC 18 oz sq yd.	Covertwo Woven PP 8 oz sq yd	Coverthree Coated PP 9 oz sq yd	Coverfour Monofil PP 6.2 oz sq yd.	Special Coverfour 27600
Tear Resistance	80 lbs x 100 lbs Federal Test Method 5134.1 (tongue tear)	155 lbs x 120 lbs ASTM D4533 (trapezoidal tear)	155 lbs x 120 lbs ASTM D4533 (trapezoidal tear)	120 lbs x 80 lbs ASTM D4533 (trapezoidal tear)	90 lbs x 65 lbs ASTM D2261 (trapezoid method)
Burst Strength Hydrostatic Pressure Resistance - (Waterproofness)	600 lbs psi Federal Test Method 5512.1	775 lbs psi ASTM D3786 Mullen Burst	775 lbs psi ASTM D3786 Mullen Burst	550 lbs psi ASTM D3786 Mullen Burst	520 lbs psi Mullen Burst
Tensile Strength	450 lbs x 400 lbs Federal Test Method 5100 Grab Tensile	450 lbs x 375 ASTM D4632 Grab Tensile	450 lbs x 375 lbs ASTM D4632 Grab Tensile	390 lbs x 280 lbs ASTM 4632 Grab Tensile	350 lbs x 280 lbs ASTM D1682
Abrasion Resistance	250 Cycles Tabor Method H-18-1000	not tested	not tested	not tested	not tested
Color	Assorted	Off White	Off White	Black	Off White
Repair Options	Thermal Weld, Hot Air Weld, Glue, Sew	Sew Only	Sew Only	Sew Only	Sew Only

Product Name and Description	Standard Sizes	****	Construction	Features
Coverone Reinforced PVC 18 oz sq yd	50 x 50 ft 50 x 80 ft 50 x 100 ft	Custom Materials, Sizes, Shapes and Constructions Available on Request	Reinforced Webbing every 12.5 ft including corners.	Standard 2" D Rings at end of Webbing. Custom Covers made to Owner's Specs.
Covertwo Woven PP 8 oz sq yd	50 x 50 ft 50 x 80 ft 50 x 100 ft		Reinforced Webbing every 12.5 ft including corners. Splices reinforced.	Standard 2" D Rings at end of Webbing. Custom Covers made to Owner's Specs.
Coverthree Coated PP 9 oz sq yd	50 x 50 ft 50 x 80 ft 50 x 100 ft		Reinforced Webbing every 12.5 ft including corners. Splices reinforced.	Standard 2" D Rings at end of Webbing. Custom Covers made to Owner's Specs.
Coverfour Monofil-PP 6.2 oz sq yd	50 x 50 ft 50 x 80 ft 50 x 100 ft		Reinforced Webbing every 12.5 ft including corners. Splices reinforced.	Standard 2" D Rings at end of Webbing. Custom Covers made to Owner's Specs.

Engineered Textile Products, Inc.

P.O. Box 7474 • 715 Loeffler Street • Mobile, Alabama 36670
 251-476-8001 • 800-222-8277 • Fax 251-476-0956